

FOREPLAY CHEAT SHEET 01/06/2013

| | |
|-------------------------|---|
| :Connect URL | Connect to a REPL server. |
| :Connect | Interactively prompt for the options to connect to a REPL server. |
| :Doc {symbol} | Show the docs for the given symbol. |
| :Javadoc {class} | Open the java docs for the given class in a browser. |
| K | Look up docs for keyword under cursor. |
| :FindDoc {arg} | Wrapper around (clojure.repl/find-doc ...). |
| :Apropos {arg} | Wrapper around (clojure.repl/apropos ...). |
| :Source {symbol} | Show the source for the given symbol. |
| [d | Show source for keyword under cursor. |
|]d | |

NAVIGATING

| | |
|-------------------------------|--|
| [<C-D> | Jump to the source of the keyword under the cursor. |
|]<C-D> | |
| <C-W><C-D> | Jump to the source of the keyword under the cursor in a split. |
| <C-W>d | |
| gf | Go to the file for the namespace under the cursor. |
| :Djump {symbol} | Jump to the definition for the given symbol. |
| :Dsplit {symbol} | Jump to the definition for the given symbol in a split. |

EVALUATING CODE

| | |
|---------------------------|---|
| :Require [ns] | Require :reload the given/current namespace. |
| :Require! [ns] | Require :reload-all the given/current namespace. |
| :Eval | Eval/print the outermost expression for the current line. |
| :{range}Eval | Eval/print the given range. |
| :Eval {expr} | Eval/print the given expression. |
| :[range]Eval! | Eval the given range or outermost expression and replace it with its result. |
| :[rng]Eval! {expr} | Eval the given expression and insert it after the given range or current line. |
| cp{motion} | Eval/print the code indicated by {motion}. |
| cpp | Eval/print the inner-most expr at the cursor. |
| cpr | Eval a require :reload form. |
| cpR | Eval a require :reload-all form. |
| c!{motion} | Eval/replace the code indicated by {motion}. |
| c!! | Eval/replace the inner-most expr at the cursor. |
| cqp | Bring up a prompt for code to eval/print. |
| cqc | Bring up a command-line-window for code to eval/print. Equivalent to cqp<C-F>i. |
| cq{motion} | Bring up a command-line-window with text indicated by {motion} prepopulated. |

INSERT MODE

| | |
|----------------------|--|
| <C-R>(| Evaluate the given expression and insert the result. |
| CTRL-X_CTRL-O | Omnicomplete |

ABOUT foreplay by Tim Pope <https://github.com/tpope>
Grab the latest version or report a bug on GitHub: <https://github.com/tpope/vim-foreplay>

Cheat sheet layout by Benjamin Peter <https://github.com/dedeibel/>